

3701206

hot street - dirt track

Mazda B6 /turbo

I-4cyl 1.6L 16v DOHC (DTH/DTH)



intake

exhaust

camshaft data:


lash ramp	: hydro	hydro
duration @ 0.1mm	: 254°	254°
duration @ 1.0mm	: 221°	221°
valve lift	: 10.15mm	10.15mm
cam lift	:	
lobe angle	: 108°	108°
timing @ 1.0mm	: 2° / 39°	38° / 3°
valve lift @ TDC	: 1.15mm	1.25mm

parts setup:

cam wheels :	:	:
follower	: O.E.M.	: O.E.M.
valve lash	: O.E.M.	: O.E.M.
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: O.E.M.	: O.E.M.
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: O.E.M.	: O.E.M.
interior spring	:	:

fitted load / length	: 20kg @ 39.5mm	: 20kg @ 39.5mm
max. load / lift	: 59kg @ 10.0mm	: 59kg @ 10.0mm

REMARKS :



REMARKS :

- # camshafts for use in 1598cc B6 engines:
 - long intake camshaft with sleeve for distributor drive
 - short exhaust camshaft
- # massflow or throttle position sensor required for reprogramming, MAP sensor will not function properly