

4341523

hot street - dirt track

Mitsubishi 4G63 evo 1-2-3

I-4cyl 2.0L 16v DOHC (RPRH/RPRH)



intake

exhaust

camshaft data:


lash ramp	: hydro	hydro
duration @ 0.1mm	: 278°	266°
duration @ 1.0mm	: 232°	223°
valve lift	: 12.00mm	11.50mm
cam lift	: 6.95mm	6.65mm
lobe angle	: 110°	110°
timing @ 1.0mm	: 3° / 49°	43° / -0°
valve lift @ TDC	: 1.30mm	1.00mm

parts setup:

cam wheels :	:	:
follower	: O.E.M.	: O.E.M.
valve lash	: O.E.M.	: O.E.M.
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: O.E.M.	: O.E.M.
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: PAC-S10011	: PAC-S10011
interior spring	:	:

fitted load / length	: 28kg @ 39.5mm	: 33kg @ 38.5mm
max. load / lift	: 92kg @ 13.0mm	: 97kg @ 13.0mm

REMARKS :



REMARKS :

- # **"type 1"** steel billet camshafts for Mitsubishi 4G63 DOHC engines (Lancer evo 1-2-3):
 - engine fitted left / gearbox right (driver's point of view)
 - ignition drive on intake camshaft
- # ONLY for dirt track applications and pro street use with adjustable engine management or carburetors