

# 5220019

tarmac rally - race

Porsche 924

I-4cyl 8v SOHC (DTx/DTx)



### intake

### exhaust

#### camshaft data:

lash ramp	: 0.20mm	0.20mm
duration @ 0.1mm	: 299°	299°
duration @ 1.0mm	: 256°	256°
valve lift	: 13.25mm	13.25mm
cam lift	:	
lobe angle	: 108°	108°
timing @ 1.0mm	: 20° / 56°	56° / 20°
valve lift @ TDC	: 4.00mm	3.90mm

#### parts setup:


cam wheels :	:	:
follower	: <b>CC048</b>	: <b>CC048</b>
valve lash	: <b>TS103</b>	: <b>TS103</b>
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: <b>not available</b>	: <b>not available</b>
lower retainer	: <b>not available</b>	: <b>not available</b>
exterior spring	: <b>not available</b>	: <b>not available</b>
interior spring	:	:

fitted load / length	: 0kg @ 0.0mm	: 0kg @ 0.0mm
max. load / lift	: 0kg @ 0.0mm	: 0kg @ 0.0mm

#### REMARKS :

# original valve spring info is not available  
valve spring kit can be developed on request  
use Catcams cam followers with lash caps for competition applications

#  
#



#### REMARKS :

- # FOR COMPETITION APPLICATIONS ONLY. Following details must be verified:
  - the camshafts must turn smooth in the cylinderhead, provide free travel by machining where needed
  - distance between valve seal and retainer at full lift must be 0.6mm at least
  - minimum valve spring travel of 1.0mm at full lift must be provided
  - distance between valve and piston 1.0mm (pref. 1.5mm). check 5-15° before TDC on exhaust, and after TDC on intake
- # ONLY for use in competition engines with independent engine management (throttle position sensor) or carburetors